NSN 5930-01-081-4765

Push Switch - Page 1 of 2

Body Style:
Panel mount
Overall Length:
0.685 inches
Overall Height:
2.600 inches
Overall Width:



View Online at https://aerobasegroup.com/nsn/5930-01-081-4765

| 0.685 inches | | | | |
|-------------------------------------------------------------------------------------------------------------------------|--|--|--|--|
| Body Length: | | | | |
| 0.685 inches | | | | |
| Body Width: | | | | |
| 0.685 inches | | | | |
| Body Height: | | | | |
| 1.450 inches | | | | |
| Case Material: | | | | |
| Plastic | | | | |
| Actuator Length: | | | | |
| 0.684 inches | | | | |
| Actuator Style: | | | | |
| Rectangular | | | | |
| Actuator Height: | | | | |
| 1.410 inches | | | | |
| Actuator Width: | | | | |
| 0.684 inches | | | | |
| Actuator Color: | | | | |
| Red single actuator | | | | |
| Illuminated Actuator Color: | | | | |
| Red single actuator | | | | |
| Actuator Inscription: | | | | |
| Security fault single actuator | | | | |
| Maximum Voltage Rating In Volts: | | | | |
| 115.0 ac and 28.0 dc | | | | |
| Inclosure Type: | | | | |
| Fully enclosed | | | | |
| Mounting Method: | | | | |
| Panel | | | | |
| Features Provided: | | | | |
| Rfi shielding | | | | |
| Nonpile-up Contact Arrangement: | | | | |
| 4 pole, double throw, one position momentary single switch unit | | | | |
| Contact Load Current Rating At Maximum Rated Voltage: | | | | |
| 2.000 amperes resistive dc and 1.000 amperes inductive dc and 2.000 amperes resistive ac and 1.000 amperes inductive ac | | | | |
| | | | | |

NSN 5930-01-081-4765

Push Switch - Page 2 of 2



| Pracious | Material | And | Location: |
|----------|----------|-----|-----------|
| Precious | wateriai | Ana | Location: |

Terminal surfaces gold

Terminal Type And Quantity:

16 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0