# NSN 5930-01-081-4768

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-081-4768
Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Corrosion resistant
Overall Length:
4.200 inches
Overall Height:
0.900 inches
Overall Width:
0.750 inches
Body Width:
0.750 inches
Body Height:
0.900 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.100 inches
Actuator Width:
0.620 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
White single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
Flight test set 82918
Mounting Surface To Terminal End Distance:
3.850 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 7.500 amperes resistive ac and 5.000 amperes inductive ac and 1.000 amperes lamp ac

# NSN 5930-01-081-4768

Push Switch - Page 2 of 2



_			_			
v.	nac	ıaı	Fea	+11	ľΩ	۰.
u	ner	ıaı	ı ca	LU		Э.

Five terminals four lamps

#### **Test Data Document:**

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Terminal Type And Quantity:**

12 socket, integrated wire termination

### **Specification Data:**

81349-mil-s-22885/77 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

No

Fiig:

A053a0