NSN 5930-01-081-5091

Hazardous Locations/environmental Protection:

125.0 milliamperes resistive load dc at sea level

Rotary Switch - Page 1 of 2

Shock proof

Overall Height:

0.232 inches

Overall Width:

0.440 inches

Shaft Diameter:

0.125 inches single actuator



View Online at https://aerobasegroup.com/nsn/5930-01-081-5091

Shaft Length:
0.250 inches single actuator
Individual Section Quantity:
1
Operating Tempurature Range:
-40.0/+185.0 degrees fahrenheit
End Application:
F15a 76301
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
6 single section in-line
Throw Quantity:
2 single section in-line
Mounting Method:
Printed circuit single mounting facility
Features Provided:
Metallic inclosure
Contact Voltage Rating In Volts:
28.0 dc at sea level
Switch Actuator Indexing Position Quantity:
2 single actuator
Shaft Type:
Round, slotted single actuator
Terminal Type:
Printed circuit
Contact Switching Action:
Breaks before makes single section in-line
Detent Rotational Torque Range:
+0.500/+8.000 inch-ounces single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:

NSN 5930-01-081-5091

Rotary Switch - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Style Designator:
In-line, cam actuated
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A052b0