Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-081-5091

Hazardous Locations/environmental Protection: Shock proof **Overall Height:** 0.232 inches **Overall Width:** 0.440 inches Shaft Diameter: 0.125 inches single actuator Shaft Length: 0.250 inches single actuator **Individual Section Quantity:** 1 **Operating Tempurature Range:** -40.0/+185.0 degrees fahrenheit **End Application:** F15a 76301 Switch Contact Basic Design: Nonpile-up symmetrical **Pole Quantity:** 6 single section in-line **Throw Quantity:** 2 single section in-line **Mounting Method:** Printed circuit single mounting facility **Features Provided:** Metallic inclosure **Contact Voltage Rating In Volts:** 28.0 dc at sea level Switch Actuator Indexing Position Quantity: 2 single actuator Shaft Type: Round, slotted single actuator **Terminal Type:** Printed circuit **Contact Switching Action:** Breaks before makes single section in-line **Detent Rotational Torque Range:** +0.500/+8.000 inch-ounces single actuator Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 125.0 milliamperes resistive load dc at sea level

## NSN 5930-01-081-5091

Rotary Switch - Page 2 of 2



**Precious Material And Location:** 

Contact surfaces gold

**Precious Material:** 

Gold

Style Designator:

In-line, cam actuated

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0