

View Online at <https://aerobasegroup.com/nsn/5930-01-081-5091>

**Hazardous Locations/environmental Protection:**

Shock proof

**Overall Height:**

0.232 inches

**Overall Width:**

0.440 inches

**Shaft Diameter:**

0.125 inches single actuator

**Shaft Length:**

0.250 inches single actuator

**Individual Section Quantity:**

1

**Operating Temperature Range:**

-40.0/+185.0 degrees fahrenheit

**End Application:**

F15a 76301

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

6 single section in-line

**Throw Quantity:**

2 single section in-line

**Mounting Method:**

Printed circuit single mounting facility

**Features Provided:**

Metallic inclosure

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round, slotted single actuator

**Terminal Type:**

Printed circuit

**Contact Switching Action:**

Breaks before makes single section in-line

**Detent Rotational Torque Range:**

+0.500/+8.000 inch-ounces single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

125.0 milliamperes resistive load dc at sea level

**Precious Material And Location:**

Contact surfaces gold

**Precious Material:**

Gold

**Style Designator:**

In-line, cam actuated

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0