

View Online at <https://aerobasegroup.com/nsn/5930-01-081-8978>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

2.070 inches

Overall Height:

0.750 inches

Overall Width:

0.750 inches

Body Diameter:

0.620 inches

Bushing Length:

0.630 inches

Body Length:

1.000 inches

Actuator Diameter:

0.380 inches

Actuator Height:

0.280 inches

Actuator Color:

Red single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc and 1.500 amperes inductive dc and 1.000 amperes lamp dc and 3.000 amperes resistive ac and 1.500 amperes inductive ac and 1.000 amperes lamp ac

Precious Material And Location:

Contacts silver and contact surfaces gold

Unable To Decode:

Unable to decode and unable to decode

Thread Series Designator:

Uns

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0