NSN 5930-01-081-8978

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-081-8978
Body Style:
Bushing mounted
Hazardous Locations/environmental Protection:
Shock resistant and vibration resistant
Overall Length:
2.070 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Body Diameter:
0.620 inches
Bushing Length:
0.630 inches
Body Length:
1.000 inches
Actuator Diameter:
0.380 inches
Actuator Height:
0.280 inches
Actuator Color:
Red single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Thready Qty Per Inch (tpi):
32
Thread Size:
0.469 inches
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
3.000 amperes resistive dc and 1.500 amperes inductive dc and 1.000 amperes lamp dc and 3.000 amperes resistive ac and 1.500 ampere
inductive ac and 1.000 amperes lamp ac
Precious Material And Location:
Contacts silver and contact surfaces gold
Unable To Decode:
Unable to decode and unable to decode

Uns

Thread Series Designator:

NSN 5930-01-081-8978

Push Switch - Page 2 of 2



Tarminal	Type	And C	Quantity:
rerminai	i vbe	Ana v	zuantity.

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0