NSN 5930-01-082-4655

Sensitive Switch - Page 1 of 1

No Fiig: A053a0



View Online at https://aerobasegroup.com/nsn/5930-01-082-4655 **Body Style:** Hole mounted **Center To Center Distance Between Mounting Facilities Parallel To Length:** 0.875 inches **Body Length:** 1.378 inches **Body Width:** 0.406 inches **Unthreaded Mounting Hole Diameter:** Between 0.113 inches and 0.116 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.406 inches **Actuator Style:** Leaf **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc **Inclosure Type:** Fully enclosed **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary single switch unit **Switch Release Force:** 3.0 ounces **Switch Actuating Force:** 16.0 ounces **Actuator Movement:** Between 0.025 pretravel inches and 0.015 overtravel inches and 0.020 differential inches **Contact Load Current Rating At Maximum Rated Voltage:** 10.000 amperes resistive dc and 5.000 amperes inductive dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac **Terminal Type And Quantity:** 3 screw Shelf Life: N/a **Unit Of Measure: Demilitarization:**