

View Online at <https://aerobasegroup.com/nsn/5930-01-082-7138>

Overall Length:

7.750 inches

Overall Height:

6.531 inches

Body Diameter:

4.937 inches

Unthreaded Mounting Hole Diameter:

0.343 inches

Distance Between Mounting Facility Centers:

4.300 inches

Pressure Switch Type:

Gage

Mounting Method:

Base and unthreaded hole

Features Provided:

Tamper proof cap

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

10.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

50.0 milliamperes inductive load third voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+0.14/+3.00 actuation point pounds per square inch and +0.03/+2.89 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

6.0 dc at sea level fourth voltage

Pressure Connector Type:

Swivel nut with compression sleeve, threaded internal single connection

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0