NSN 5930-01-082-7138

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-082-7138

Overall Length:
7.750 inches
Overall Height:
6.531 inches
Body Diameter:
4.937 inches
Unthreaded Mounting Hole Diameter:
0.343 inches
Distance Between Mounting Facility Centers:
4.300 inches
Pressure Switch Type:
Gage
Mounting Method:
Base and unthreaded hole
Features Provided:
Tamper proof cap
Thready Qty Per Inch (tpi):
18 single pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
10.00 pounds per square inch
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
50.0 milliamperes inductive load third voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+0.14/+3.00 actuation point pounds per square inch and +0.03/+2.89 deactuation point pounds per square inch
Contact Adjustment Type:
External deactuation point screw and external actuation point screw
Contact Voltage Rating In Volts:
6.0 dc at sea level fourth voltage

Pressure Connector Type:

Swivel nut with compression sleeve, threaded internal single connection

NSN 5930-01-082-7138

Pressure Switch - Page 2 of 2



Ī	hread	Series	Desig	nator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0