

View Online at <https://aerobasegroup.com/nsn/5930-01-082-9586>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Corrosion resistant

Overall Length:

2.375 inches

Overall Height:

1.030 inches

Overall Width:

1.030 inches

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Height:

0.375 inches

Actuator Free Position Height:

1.375 inches

Housing Diameter:

1.030 inches

Housing Length:

1.100 inches

Housing Bushing Length:

1.000 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

80.0 ounces

Switch Actuating Force:

144.0 ounces

Actuator Movement:

Between 0.070 pretravel inches and 0.250 overtravel inches and 0.035 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 4.000 amperes inductive dc and 3.000 amperes lamp dc and 6.000 amperes motor dc

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Terminal Type And Quantity:

6 wire lead

Specification Data:

81349-mil-s-8805/100 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0