NSN 5930-01-083-1243

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-083-1243

| Body Style: | |
|---|--|
| Panel mount | |
| Overall Length: | |
| Between 0.750 inches and 0.760 inches | |
| Overall Height: | |
| 2.770 inches | |
| Overall Width: | |
| Between 0.750 inches and 0.760 inches | |
| Body Length: | |
| 0.688 inches | |
| Body Width: | |
| 0.688 inches | |
| Body Height: | |
| 2.500 inches | |
| Case Material: | |
| Metal | |
| Actuator Length: | |
| Between 0.500 inches and 0.560 inches | |
| Actuator Style: | |
| Rectangular | |
| Actuator Height: | |
| 0.150 inches | |
| Actuator Width: | |
| Between 0.500 inches and 0.560 inches | |
| Actuator Color: | |
| White single actuator and white single actuator | |
| Illuminated Actuator Color: | |
| White single actuator and white single actuator | |
| Actuator Inscription: | |
| Cable/radar single actuator | |
| Maximum Voltage Rating In Volts: | |
| 115.0 ac and 28.0 dc | |
| Inclosure Type: | |
| Fully enclosed | |
| Mounting Method: | |
| Panel | |
| Features Provided: | |
| Rfi shielding | |
| Nonpile-up Contact Arrangement: | |
| 4 pole, double throw, three positions maintained single switch unit | |
| Contact Load Current Rating At Maximum Rated Voltage: | |

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

NSN 5930-01-083-1243

Push Switch - Page 2 of 2



| Special | Features: |
|----------------|-----------|
|----------------|-----------|

Includes four terminals for lamps and one common

Terminal Type And Quantity:

17 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A053a0