NSN 5930-01-083-3058

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-083-3058

| Hazardous Locations/environmental Protection: |
|---|
| Watertight |
| Overall Height: |
| 2.906 inches |
| Overall Width: |
| 2.812 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.221 inches single mounting facility |
| Individual Section Quantity: |
| 2 |
| Knob Manufacturer Code: |
| 82121 |
| Knob Manufacturer Part Number: |
| G |
| Longest Horizontal Distance Between Mounting Centers: |
| 2.000 inches single mounting facility |
| Shortest Horizontal Distance Between Mounting Centers: |
| 1.000 inches single mounting facility |
| Longest Vertical Distance Between Mounting Centers: |
| 2.188 inches single mounting facility |
| Switch Contact Basic Design: |
| Nonpile-up symmetrical |
| Pole Quantity: |
| 1 each section rear |
| Throw Quantity: |
| 3 each section rear |
| Mounting Method: |
| Unthreaded hole single mounting facility |
| Features Provided: |
| Actuator knob |
| Contact Voltage Rating In Volts: |
| 500.0 highest ac voltage rating at sea level |
| Switch Actuator Momentary Position: |
| Counterclockwise single actuator |
| Mounting Facility Pattern: |
| Isosceles triangle single mounting facility |
| Switch Actuator Indexing Position Quantity: |
| 3 single actuator |
| Terminal Type: |
| Tab w/screw |
| |

Contact Switching Action:

Makes before breaks each section rear

NSN 5930-01-083-3058

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load highest ac voltage rating at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0