## NSN 5930-01-084-0803

Sensitive Switch - Page 1 of 2

**Body Style:** 



View Online at https://aerobasegroup.com/nsn/5930-01-084-0803

| Hole mounted   |
|--|
| Overall Length:  |
| 1.940 inches   |
| Center To Center Distance Between Mounting Facilities Parallel To Length:                |
| 1.000 inches   |
| Overall Width:   |
| 0.690 inches   |
| Body Length:   |
| 1.940 inches   |
| Body Width:  |
| 0.690 inches   |
| Body Height:   |
| 0.950 inches   |
| Case Material:   |
| Plastic  |
| Unthreaded Mounting Hole Diameter:   |
| 0.140 inches   |
| Actuator Style:  |
| Round  |
| Actuator Diameter:   |
| 0.160 inches   |
| Actuator Free Position Height:   |
| 0.630 inches   |
| Maximum Voltage Rating In Volts:   |
| 30.0 dc  |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Method:   |
| Unthreaded hole  |
| Nonpile-up Contact Arrangement:  |
| 1 pole, double throw, one position momentary single switch unit                          |
| Switch Release Force:  |
| 4.0 grams  |
| Switch Actuating Force:  |
| Between 9.0 grams and 15.0 grams   |
| Actuator Movement:   |
| Between 0.015 pretravel inches and 0.005 overtravel inches and 0.002 differential inches |
| Contact Load Current Rating At Maximum Rated Voltage:                                    |
| 15.000 amperes resistive dc and 10.000 amperes inductive dc                              |
| Terminal Type And Quantity:  |

3 screw

## NSN 5930-01-084-0803

Sensitive Switch - Page 2 of 2



| _ |    |      |   |        |  |
|---|----|------|---|--------|--|
| c | hο | JIF. |   | .ife:  |  |
| J |    |      | _ | .II C. |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0