

View Online at <https://aerobasegroup.com/nsn/5930-01-084-2967>

Thread Class:

3b single pressure connection

Inside Diameter:

0.438 inches single connection

Hazardous Locations/environmental Protection:

Dusttight

Overall Length:

2.470 inches

Body Length:

1.920 inches

Overall Diameter:

0.750 inches

End Application:

Control unit 97499

Pressure Switch Type:

Gage

Width Across Flats:

0.750 inches

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit

Mounting Method:

Terminal

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

2250.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

1.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

140.00 actuation point pounds per square inch gage and 100.00 deactuation point pounds per square inch gage and 40.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

18.0 dc at sea level single voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0