NSN 5930-01-084-5687

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-084-5687

Padu Stulai
Body Style: Hole mounted
Overall Length:
1.875 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.875 inches
Overall Height:
0.406 inches
Overall Width:
0.625 inches
Body Length:
1.094 inches
Body Width:
0.406 inches
Body Height:
0.625 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.114 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.406 inches
Actuator Length:
0.110 inches
Actuator Style:
Rectangular
Actuator Height:
0.063 inches
Actuator Free Position Height:
0.578 inches
Maximum Voltage Rating In Volts:
250.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:

112.0 grams

Switch Actuating Force:

285.0 grams

NSN 5930-01-084-5687

Sensitive Switch - Page 2 of 2



Δ	ctu	ato	- М	ΛV/	ama	۵ni	ŀ
н	CLU	alu	IVI	OVE	2111		L.

Between 0.047 pretravel inches and 0.050 overtravel inches and 0.010 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive ac

Precious Material And Location:

Contact surfaces silver

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0