

View Online at <https://aerobasegroup.com/nsn/5930-01-084-5756>

Hazardous Locations/environmental Protection:

Dusttight

Overall Length:

2.156 inches

Overall Height:

4.406 inches

Overall Width:

2.260 inches

Capillary Tube Length:

72.0 inches

Bulb Length:

4.000 inches

Bulb Diameter:

0.375 inches

Longest Horizontal Distance Between Mounting Centers:

1.562 inches

Longest Vertical Distance Between Mounting Centers:

2.938 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Operating Temperature Rating:

140.0 degrees fahrenheit

Mounting Method:

Surface and slot

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

7.2 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

-30.00/+50.00 actuation point degrees fahrenheit and -28.00/+48.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point knob with scale and external actuation point knob with scale

Contact Voltage Rating In Volts:

277.0 ac at sea level first voltage

Media For Which Designed:

Gas

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0