

View Online at <https://aerobasegroup.com/nsn/5930-01-084-6579>

Inside Diameter:

0.250 inches single connection

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

4.250 inches

Overall Height:

4.625 inches

Overall Width:

2.281 inches

Body Length:

3.562 inches

Body Height:

2.500 inches

Unthreaded Mounting Hole Diameter:

0.250 inches

Longest Horizontal Distance Between Mounting Centers:

4.219 inches

Longest Vertical Distance Between Mounting Centers:

1.875 inches

End Application:

4120-01-047-3950

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -40.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

150.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

5.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+1.00/+104.00 actuation point pounds per square inch and +0.00/+100.00 deactuation point pounds per square inch

Contact Adjustment Type:

Internal deactuation point hex nut and internal actuation point hex nut

Contact Voltage Rating In Volts:

230.0 ac at sea level first voltage

Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

60.0 second voltage

Media For Which Designed:

Gas

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0