## NSN 5930-01-084-6607

Sensitive Switch - Page 1 of 2

**Body Style:** 



View Online at https://aerobasegroup.com/nsn/5930-01-084-6607

Hole mounted
Overall Length:
0.781 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Overall Height:
0.823 inches
Overall Width:
0.250 inches
Body Length:
0.781 inches
Body Width:
0.250 inches
Body Height:
0.493 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Style:
Round
Actuator Width:
0.130 inches
Actuator Free Position Height:
0.455 inches
Maximum Voltage Rating In Volts:
30.0 dc
End Application:
Tt-2423 80058
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
2.0 grams
Switch Actuating Force:
12.0 grams
Actuator Movement:
Between 0.120 pretravel inches and 0.026 overtravel inches and 0.016 differential inches

## NSN 5930-01-084-6607

Sensitive Switch - Page 2 of 2



	Contact Load	Current	Rating	At Ma	aximum	Rated	Voltage:
--	--------------	---------	--------	-------	--------	-------	----------

5.000 amperes resistive dc and 3.000 amperes inductive dc

**Precious Material And Location:** 

Contacts silver

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0