

View Online at <https://aerobasegroup.com/nsn/5930-01-084-6607>

**Body Style:**

Hole mounted

**Overall Length:**

0.781 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.375 inches

**Overall Height:**

0.823 inches

**Overall Width:**

0.250 inches

**Body Length:**

0.781 inches

**Body Width:**

0.250 inches

**Body Height:**

0.493 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.088 inches

**Actuator Style:**

Round

**Actuator Width:**

0.130 inches

**Actuator Free Position Height:**

0.455 inches

**Maximum Voltage Rating In Volts:**

30.0 dc

**End Application:**

Tt-2423 80058

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

2.0 grams

**Switch Actuating Force:**

12.0 grams

**Actuator Movement:**

Between 0.120 pretravel inches and 0.026 overtravel inches and 0.016 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc

**Precious Material And Location:**

Contacts silver

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A053a0