# NSN 5930-01-084-6607

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-084-6607

Body	Style:
------	--------

Hole mounted

**Overall Length:** 

0.781 inches

### Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

#### **Overall Height:**

0.823 inches

#### **Overall Width:**

0.250 inches

**Body Length:** 

#### 0.781 inches

Body Width:

#### 0.250 inches

Body Height:

#### 0.493 inches

Case Material:

Plastic

#### **Unthreaded Mounting Hole Diameter:**

0.088 inches

#### **Actuator Style:**

Round

#### Actuator Width:

0.130 inches

#### **Actuator Free Position Height:**

0.455 inches

#### Maximum Voltage Rating In Volts:

30.0 dc

#### End Application:

Tt-2423 80058

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Unthreaded hole

#### Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

#### Switch Release Force:

2.0 grams

## Switch Actuating Force:

12.0 grams

#### **Actuator Movement:**

Between 0.120 pretravel inches and 0.026 overtravel inches and 0.016 differential inches

# NSN 5930-01-084-6607

Sensitive Switch - Page 2 of 2



## Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc

## **Precious Material And Location:**

Contacts silver

## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

## Demilitarization:

No

## Fiig:

A053a0