NSN 5930-01-084-9256

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-084-9256

Body Style:
Bushing mounted
Hazardous Locations/environmental Protection:
Moisture resistant
Overall Length:
2.295 inches
Overall Height:
0.720 inches
Overall Width:
0.720 inches
Body Diameter:
0.720 inches
Body Length:
1.000 inches
Case Material:
Metal
Actuator Style:
Roller plunger
Actuator Free Position Height:
1.295 inches
Actuator Roller Diameter:
0.375 inches
Actuator Roller Width:
0.120 inches
Maximum Voltage Rating In Volts:
28.0 dc
End Application:
F-15, t-37, t-38, u-2 airframe
Inclosure Type:
Hermetically sealed
Mounting Method:
Threaded bushing
Features Provided:
Actuator seal
Thready Qty Per Inch (tpi):
32
Thread Size:
0.469 inches
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Switch Release Force:

64.0 ounces

NSN 5930-01-084-9256 Sensitive Switch - Page 2 of 2



Criticality Code Justification:
Feat
Switch Actuating Force:
144.0 ounces
Actuator Movement:
Between 0.040 pretravel inches and 0.125 overtravel inches and 0.020 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
7.000 amperes resistive dc and 4.000 amperes inductive dc and 4.000 amperes motor dc
Special Features:
Weapon system essential
Thread Series Designator:
Uns
Terminal Type And Quantity:
6 wire lead
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A053a0