NSN 5930-01-085-0061

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-085-0061

Rody Style:
Body Style: Hole mounted
Hazardous Locations/environmental Protection:
Shock resistant
Overall Length:
1.594 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.875 inches
Overall Height:
0.820 inches
Overall Width:
0.400 inches
Body Length:
1.094 inches
Body Width:
0.400 inches
Body Height:
0.625 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.114 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.406 inches
Actuator Length:
0.110 inches
Actuator Style:
Rectangular
Actuator Height:
0.109 inches
Actuator Width:
0.165 inches
Actuator Free Position Height:
0.625 inches
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

NSN 5930-01-085-0061 Sensitive Switch - Page 2 of 2



Switch Release Force:
4.0 inch-ounces
Switch Actuating Force:
15.0 grams
Actuator Movement:
Between 0.047 pretravel inches and 0.050 overtravel inches and 0.010 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
500.000 milliamperes resistive dc
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A053a0