

View Online at <https://aerobasegroup.com/nsn/5930-01-085-3351>

Overall Length:

1.045 inches

Overall Height:

1.528 inches

Overall Width:

1.000 inches

Body Length:

0.425 inches

Unthreaded Mounting Hole Diameter:

0.132 inches

Distance Between Mounting Facility Centers:

1.281 inches

Pressure Switch Type:

Differential

Operating Temperature Rating:

Between 32.0 degrees fahrenheit and 140.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

25.00 pounds per square inch gage

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Quick disconnect, male

Contact Load Current Rating:

50.0 milliamperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+0.50/+300.00 actuation point inches of water and +0.50/+300.00 deactuation point inches of water

Contact Adjustment Type:

Internal actuation point screw and internal deactuation point screw

Contact Voltage Rating In Volts:

5.0 ac at sea level single voltage

Pressure Connector Type:

Tapered, butt weld all connections

Media For Which Designed:

Gas

Precious Material And Location:

Contacts gold

Precious Material:

Gold

Style Designator:

Rectangular w/bracket

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0