NSN 5930-01-085-3356

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-085-3356

External deactuation point screw and external actuation point screw

Overall Length:
10.562 inches
Overall Height:
3.062 inches
Overall Width:
0.875 inches
Body Diameter:
0.375 inches
Body Length:
9.000 inches
Distance Between Mounting Facility Centers:
0.312 inches
Bulb Length:
9.000 inches
Bulb Diameter:
0.375 inches
Tempurature Sensing Element Type:
Bulb
Operating Tempurature Rating:
1200.0 degrees fahrenheit
Mounting Method:
Immersion well and threaded hole
Thready Qty Per Inch (tpi):
20 all threaded hole
Contact Action Stimulus:
Increase
Thread Size:
0.138 inches all threaded hole
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, double break/double make, one position momentary
Terminal Type:
Tab w/screw
Contact Load Current Rating:
7.5 amperes resistive load single voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+35.00/+750.00 actuation point degrees fahrenheit and +35.00/+750.00 deactuation point degrees fahrenheit
Contact Adjustment Type:

NSN 5930-01-085-3356

Thermostatic Switch - Page 2 of 2



Contact Voltage Rating In Volts:	Contact	Voltage	Rating	In	Volts
----------------------------------	---------	---------	--------	----	-------

120.0 ac at sea level single voltage

Media For Which Designed:

Gas or liquid

Thread Series Designator:

Uns all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0