## NSN 5930-01-085-4573

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-085-4573

Body Style:
Hole mounted
Overall Length:
1.360 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.040 inches
Overall Height:
0.765 inches
Overall Width:
0.406 inches
Body Length:
1.090 inches
Body Width:
0.406 inches
Body Height:
0.630 inches
Case Material:
Plastic
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.410 inches
Actuator Length:
0.110 inches
Actuator Style:
Rectangular
Actuator Height:
0.084 inches
Actuator Free Position Height:
0.194 inches
Actuator Adapter Style:
Leaf
Maximum Voltage Rating In Volts:
250.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
0.21 ounces
Switch Actuating Force:

2.6 ounces

## NSN 5930-01-085-4573

Sensitive Switch - Page 2 of 2



## **Actuator Movement:**

Between 0.120 pretravel inches and 0.090 overtravel inches and 0.032 differential inches

## **Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 6.000 amperes inductive dc and 250.000 milliamperes resistive ac

**Precious Material And Location:** 

Contacts silver

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0