NSN 5930-01-085-5532

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-085-5532

Thread Class:

2a single mounting facility

Thread Length:

0.468 inches single mounting facility

Overall Length:

2.093 inches

Overall Height:

1.750 inches

Overall Width:

1.375 inches

First Flat Length:

0.406 inches single actuator

Flat Height:

Shaft Diameter:

0.250 inches single actuator

0.199 inches single actuator

Shaft Length:

0.500 inches single actuator

Individual Section Quantity:

1

Nonturn Device Type:

Slotted bushing at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.469 inches single mounting facility

Contact Voltage Rating In Volts:

250.0 ac at sea level

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

NSN 5930-01-085-5532

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

7.5 amperes resistive load ac at sea level

Style Designator:

Square wafer, panel mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0