## NSN 5930-01-085-6257

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-085-6257

**Thread Class:** 

2a single mounting facility

Thread Length:

0.406 inches single mounting facility

**Overall Length:** 

3.812 inches

**Overall Height:** 

2.312 inches

**Overall Width:** 

1.968 inches

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

2.000 inches single actuator

**Nonturn Device Radius:** 

0.531 inches at 1: 45 o'clock

**Individual Section Quantity:** 

2

**Nonturn Device Type:** 

Tab at 1: 45 o'clock

**Operating Tempurature Range:** 

-65.0/+100.0 degrees celsius

**End Application:** 

Sins mk2 94756

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

Pole Quantity:

1 each section front

**Throw Quantity:** 

24 each section rear

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

**Rotor Through Connection Quantity:** 

1 each section

**Switch Actuator Indexing Position Quantity:** 

24 single actuator

**Shaft Type:** 

Round, breakoff single actuator

## NSN 5930-01-085-6257

Rotary Switch - Page 2 of 2



Terminal Type:
Tab, solder lug
Contact Switching Action:
Breaks before makes each section rear
<b>Switch Actuator Positioning Increment:</b>
15.0 degrees single actuator
Switch Actuator Stop Device Type:
Adjustable stop single actuator
Contact Load Current Rating:
1.0 amperes resistive load ac at sea level
Precious Material And Location:
Contacts and rotors blades silver
Precious Material:
Silver
Style Designator:
Circular wafer, bushing mount
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A052b0