

View Online at <https://aerobasegroup.com/nsn/5930-01-085-6544>

Body Style:

Hole mount

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.156 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.937 inches

Overall Height:

1.031 inches

Overall Width:

0.450 inches

Body Length:

0.500 inches

Body Width:

0.450 inches

Body Height:

0.455 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.094 inches

Actuator Style:

Rectangular

Actuator Height:

0.531 inches

Actuator Width:

0.093 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Actuator Color:

Natural single actuator

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

End Application:

An/alr-46 15786

Mounting Surface To Terminal End Distance:

0.550 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes resistive ac

Precious Material And Location:

Terminals and contact surfaces silver

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0