# NSN 5930-01-085-6544

Toggle Switch - Page 1 of 2

Unthreaded hole



View Online at https://aerobasegroup.com/nsn/5930-01-085-6544

| Body Style: Hole mount  Hazardous Locations/environmental Protection:  Dustproof Overall Length:  1.156 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 0.937 inches Overall Height: 1.031 inches Overall Width: 0.450 inches Body Length: 0.500 inches Body Width: 0.450 inches Body Height: 0.455 inches Case Material: Plastic Unthreaded Mounting Hole Diameter: 0.094 inches Actuator Style: Rectangular Actuator Height: 0.531 inches |
|--|
| Hazardous Locations/environmental Protection:  Dustproof Overall Length:  1.156 inches Center To Center Distance Between Mounting Facilities Parallel To Length:  0.937 inches Overall Height:  1.031 inches Overall Width:  0.450 inches Body Length:  0.500 inches Body Width:  0.450 inches Body Height:  0.455 inches Case Material:  Plastic Unthreaded Mounting Hole Diameter:  0.094 inches Actuator Style: Rectangular Actuator Height:                              |
| Dustproof Overall Length:  1.156 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 0.937 inches Overall Height: 1.031 inches Overall Width: 0.450 inches Body Length: 0.500 inches Body Width: 0.450 inches Body Height: 0.455 inches Case Material: Plastic Unthreaded Mounting Hole Diameter: 0.094 inches Actuator Style: Rectangular Actuator Height:   |
| Overall Length:  1.156 inches  Center To Center Distance Between Mounting Facilities Parallel To Length:  0.937 inches  Overall Height:  1.031 inches  Overall Width:  0.450 inches  Body Length:  0.500 inches  Body Width:  0.450 inches  Body Height:  0.455 inches  Case Material:  Plastic  Unthreaded Mounting Hole Diameter:  0.094 inches  Actuator Style:  Rectangular  Actuator Height:  |
| 1.156 inches  Center To Center Distance Between Mounting Facilities Parallel To Length: 0.937 inches  Overall Height: 1.031 inches  Overall Width: 0.450 inches  Body Length: 0.500 inches  Body Width: 0.450 inches  Body Height: 0.455 inches  Case Material: Plastic  Unthreaded Mounting Hole Diameter: 0.094 inches  Actuator Style: Rectangular  Actuator Height:  |
| Center To Center Distance Between Mounting Facilities Parallel To Length:  0.937 inches  Overall Height:  1.031 inches  Overall Width:  0.450 inches  Body Length:  0.500 inches  Body Width:  0.450 inches  Body Height:  0.455 inches  Case Material:  Plastic  Unthreaded Mounting Hole Diameter:  0.094 inches  Actuator Style:  Rectangular  Actuator Height:   |
| Overall Height: 1.031 inches Overall Width: 0.450 inches Body Length: 0.500 inches Body Width: 0.450 inches Body Height: 0.455 inches Case Material: Plastic Unthreaded Mounting Hole Diameter: 0.094 inches Actuator Style: Rectangular Actuator Height:  |
| Overall Height:  1.031 inches  Overall Width:  0.450 inches  Body Length:  0.500 inches  Body Width:  0.450 inches  Body Height:  0.455 inches  Case Material:  Plastic  Unthreaded Mounting Hole Diameter:  0.094 inches  Actuator Style:  Rectangular  Actuator Height:  |
| 1.031 inches  Overall Width:  0.450 inches  Body Length:  0.500 inches  Body Width:  0.450 inches  Body Height:  0.455 inches  Case Material:  Plastic  Unthreaded Mounting Hole Diameter:  0.094 inches  Actuator Style:  Rectangular  Actuator Height:   |
| Overall Width:  0.450 inches  Body Length:  0.500 inches  Body Width:  0.450 inches  Body Height:  0.455 inches  Case Material:  Plastic  Unthreaded Mounting Hole Diameter:  0.094 inches  Actuator Style:  Rectangular  Actuator Height:   |
| 0.450 inches  Body Length: 0.500 inches  Body Width: 0.450 inches  Body Height: 0.455 inches  Case Material: Plastic  Unthreaded Mounting Hole Diameter: 0.094 inches  Actuator Style: Rectangular  Actuator Height:   |
| Body Length:  0.500 inches  Body Width:  0.450 inches  Body Height:  0.455 inches  Case Material:  Plastic  Unthreaded Mounting Hole Diameter:  0.094 inches  Actuator Style:  Rectangular  Actuator Height:   |
| 0.500 inches  Body Width: 0.450 inches  Body Height: 0.455 inches  Case Material: Plastic  Unthreaded Mounting Hole Diameter: 0.094 inches  Actuator Style: Rectangular  Actuator Height:  |
| Body Width:  0.450 inches  Body Height:  0.455 inches  Case Material:  Plastic  Unthreaded Mounting Hole Diameter:  0.094 inches  Actuator Style:  Rectangular  Actuator Height:   |
| 0.450 inches  Body Height: 0.455 inches  Case Material: Plastic  Unthreaded Mounting Hole Diameter: 0.094 inches  Actuator Style: Rectangular  Actuator Height:  |
| Body Height:  0.455 inches  Case Material:  Plastic  Unthreaded Mounting Hole Diameter:  0.094 inches  Actuator Style:  Rectangular  Actuator Height:  |
| 0.455 inches  Case Material:  Plastic  Unthreaded Mounting Hole Diameter:  0.094 inches  Actuator Style:  Rectangular  Actuator Height:  |
| Case Material: Plastic Unthreaded Mounting Hole Diameter: 0.094 inches Actuator Style: Rectangular Actuator Height:  |
| Plastic Unthreaded Mounting Hole Diameter: 0.094 inches Actuator Style: Rectangular Actuator Height:   |
| Unthreaded Mounting Hole Diameter:  0.094 inches  Actuator Style:  Rectangular  Actuator Height:   |
| 0.094 inches  Actuator Style:  Rectangular  Actuator Height:   |
| Actuator Style: Rectangular Actuator Height:   |
| Rectangular  Actuator Height:  |
| Actuator Height:   |
| -  |
| 0.531 inches   |
|  |
| Actuator Width:  |
| 0.093 inches   |
| Actuator Position-action Relationship:   |
| Up position momentary and down position momentary and center position maintained   |
| Actuator Color:  |
| Natural single actuator  |
| Maximum Voltage Rating In Volts:   |
| 250.0 ac and 28.0 dc   |
| End Application:   |
| An/alr-46 15786  |
| Mounting Surface To Terminal End Distance:   |
| 0.550 inches   |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Method:   |

# NSN 5930-01-085-6544

Toggle Switch - Page 2 of 2



#### **Nonpile-up Contact Arrangement:**

1 pole, double throw, two positions momentary single switch unit

## **Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 2.000 amperes resistive ac

#### **Precious Material And Location:**

Terminals and contact surfaces silver

## **Terminal Type And Quantity:**

6 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0