# NSN 5930-01-085-6545

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-085-6545

### Body Style:

Hole mounted

#### Hazardous Locations/environmental Protection:

Flame resistant

#### **Overall Length:**

0.300 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

0.150 inches

#### **Overall Height:**

0.400 inches

#### **Overall Width:**

0.100 inches

#### **Body Length:**

0.300 inches

#### Body Width:

0.100 inches

## Body Height:

Body Holght.

### 0.250 inches

Case Material:

Plastic

#### **Unthreaded Mounting Hole Diameter:**

0.059 inches

#### Actuator Style:

Round

#### Actuator Diameter:

0.038 inches

#### **Actuator Free Position Height:**

0.220 inches

#### Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

#### **End Application:**

Attack cnsl m 36090

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Unthreaded hole

#### Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

#### Switch Release Force:

75.0 ounces

#### Switch Actuating Force:

4.0 ounces

# NSN 5930-01-085-6545

Sensitive Switch - Page 2 of 2



#### **Actuator Movement:**

Between 0.015 pretravel inches and 0.003 overtravel inches and 0.004 differential inches

#### Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.000 amperes inductive dc and 2.000 amperes resistive ac

#### **Precious Material And Location:**

Contacts silver

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0