NSN 5930-01-085-6545

Sensitive Switch - Page 1 of 2

4.0 ounces



View Online at https://aerobasegroup.com/nsn/5930-01-085-6545

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Flame resistant
Overall Length:
0.300 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.150 inches
Overall Height:
0.400 inches
Overall Width:
0.100 inches
Body Length:
0.300 inches
Body Width:
0.100 inches
Body Height:
0.250 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.059 inches
Actuator Style:
Round
Actuator Diameter:
0.038 inches
Actuator Free Position Height:
0.220 inches
Maximum Voltage Rating In Volts:
250.0 ac and 30.0 dc
End Application:
Attack cnsl m 36090
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
75.0 ounces
Switch Actuating Force:

NSN 5930-01-085-6545

Sensitive Switch - Page 2 of 2



Actuator Movement:

Between 0.015 pretravel inches and 0.003 overtravel inches and 0.004 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.000 amperes inductive dc and 2.000 amperes resistive ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0