

View Online at <https://aerobasegroup.com/nsn/5930-01-085-6551>

**Body Style:**

Panel mounted

**Hazardous Locations/environmental Protection:**

Corrosion resistant

**Overall Length:**

2.450 inches

**Overall Height:**

1.000 inches

**Overall Width:**

0.750 inches

**Body Width:**

0.655 inches

**Body Height:**

0.905 inches

**Case Material:**

Metal

**Actuator Length:**

0.680 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.188 inches

**Actuator Width:**

0.430 inches

**Actuator Color:**

White single actuator and white single actuator

**Illuminated Actuator Color:**

White single actuator and white single actuator

**Illuminated Actuator Color Sequence:**

Top half of actuator white bottom half of actuator white

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

4920-01-064-9497

**Mounting Surface To Terminal End Distance:**

2.200 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

3.000 amperes resistive dc and 1.500 amperes inductive dc and 1.500 amperes lamp dc and 3.000 amperes resistive ac and 1.500 amperes inductive ac and 1.000 amperes lamp ac

**Special Features:**

Lens split horizontally

**Test Data Document:**

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

9 tab, solder lug

**Specification Data:**

81349-mil-s-22885/58 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0