NSN 5930-01-085-6555

Push Switch - Page 1 of 2

Test Data Document:



View Online at https://aerobasegroup.com/nsn/5930-01-085-6555

view offilite at https://defobasegroup.com/hish/0330-01-003-0000
Body Style:
Panel mounted
Overall Length:
2.450 inches
Overall Height:
1.000 inches
Overall Width:
0.750 inches
Body Width:
0.655 inches
Body Height:
0.905 inches
Actuator Length:
0.680 inches
Actuator Style:
Rectangular
Actuator Height:
0.188 inches
Actuator Width:
0.430 inches
Actuator Color:
White single actuator and red single actuator
Illuminated Actuator Color:
White single actuator and red single actuator
Illuminated Actuator Color Sequence:
Top half of actuator white and bottom half red
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
2.200 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
3.000 amperes resistive dc and 1.500 amperes inductive dc and 1.500 amperes lamp dc and 3.000 amperes resistive ac and 1.500 amperes
inductive ac and 1.000 amperes lamp ac
Special Features:
Horizontal split display

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

NSN 5930-01-085-6555

Push Switch - Page 2 of 2



Terminal Type And Quantity:
9 tab, solder lug
Specification Data:
81349-mil-s-22885/58 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0