## NSN 5930-01-085-6556

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-085-6556

- **Body Style:**
- Panel mounted
- **Overall Length:**
- 2.450 inches
- **Overall Height:**
- 1.000 inches
- **Overall Width:**
- 0.750 inches
- **Body Width:**
- 0.655 inches
- **Body Height:**
- 0.905 inches
- Actuator Length:
- 0.680 inches
- Actuator Style:

## Rectangular

- Actuator Height:
- 0.188 inches
- Actuator Width:
- 0.430 inches
- Actuator Color:
- White single actuator
- Illuminated Actuator Color:
- White single actuator
- Maximum Voltage Rating In Volts:
- 115.0 ac and 28.0 dc
- Mounting Surface To Terminal End Distance:
- 2.200 inches
- Inclosure Type:
- Fully enclosed
- **Mounting Method:**
- Panel
- Nonpile-up Contact Arrangement:
- 4 pole, double throw, one position momentary single switch unit

#### Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc and 1.500 amperes inductive dc and 1.500 amperes lamp dc and 3.000 amperes resistive ac and 1.500 amperes inductive ac and 1.000 amperes lamp ac

#### **Special Features:**

15 tob colder lug

Full display lens

**Test Data Document:** 

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### Terminal Type And Quantity:

# NSN 5930-01-085-6556

Push Switch - Page 2 of 2



**Specification Data:** 

81349-mil-s-22885/58 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0