

View Online at <https://aerobasegroup.com/nsn/5930-01-086-2228>

Thread Class:

2a single mounting facility

Thread Length:

0.380 inches single mounting facility

Overall Length:

3.130 inches

First Flat Length:

0.380 inches single actuator

Flat Height:

0.190 inches single actuator

Shaft Diameter:

0.245 inches single actuator and 0.251 inches single actuator

Shaft Length:

0.500 inches single actuator

Overall Diameter:

1.270 inches

Nonturn Device Radius:

0.530 inches at 6: 00 o'clock

Individual Section Quantity:

3

Nonturn Device Type:

Tab at 6: 00 o'clock

Operating Temperature Range:

-65.0/+85.0 degrees celsius

End Application:

6920-00-179-7320

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section rear

Throw Quantity:

4 each section rear

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

300.0 highest ac voltage rating at sea level

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks 2nd section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Detent Rotational Torque Range:

+1.000/+6.000 inch-pounds single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load dc at sea level and 50.0 milliamperes inductive load dc at sea level

Precious Material And Location:

Contact surfaces gold and contacts silver

Precious Material:

Gold and silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0