

View Online at <https://aerobasegroup.com/nsn/5930-01-086-6471>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

0.512 inches

**Overall Height:**

1.652 inches

**Overall Width:**

0.701 inches

**Bushing Length:**

0.315 inches

**Body Length:**

0.512 inches

**Body Width:**

0.701 inches

**Body Height:**

0.452 inches

**Case Material:**

Plastic

**Actuator Style:**

Round

**Actuator Diameter:**

0.217 inches

**Actuator Height:**

0.650 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position maintained

**Actuator Position-locking Relationship:**

Up position locked in and down position locked in and center position no locking action

**Actuator Color:**

Natural single actuator

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**End Application:**

An/paq-t1 12934

**Mounting Surface To Terminal End Distance:**

0.609 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, three positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc and 3.000 amperes resistive ac

**Precious Material And Location:**

Terminals gold and contacts silver

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0