

View Online at <https://aerobasegroup.com/nsn/5930-01-086-7052>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Explosion proof and watertight

Overall Length:

3.000 inches

Overall Width:

2.400 inches

Actuator Style:

Roller arm

Actuator Roller Diameter:

0.750 inches

Actuator Roller Width:

0.320 inches

Housing Height:

2.400 inches

Housing Length:

4.350 inches

Housing Width:

3.000 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

3.500 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

2.360 inches

Maximum Voltage Rating In Volts:

440.0 ac and 355.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

32.0 ounces

Actuator Movement:

10.0 pretravel degrees and 4.0 overtravel degrees and 2.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

100.000 milliamperes resistive dc and 6.000 amperes resistive ac

Terminal Type And Quantity:

3 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0