## NSN 5930-01-086-7484

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-086-7484

## Thread Class:

2a single mounting facility

## Thread Length:

 $0.370 \ \text{inches} \ \text{single} \ \text{mounting} \ \text{facility} \ \text{and} \ 0.380 \ \text{inches} \ \ \text{single} \ \text{mounting} \ \text{facility}$ 

## Overall Length:

2.985 inches

## **Overall Diameter:**

2.070 inches

## Individual Section Quantity:

1

#### Knob Manufacturer Code:

13445

#### Knob Manufacturer Part Number:

80101-c

#### Nonturn Device Type:

Flatted bushing at 12: 00 o'clock

#### Switch Contact Basic Design:

Nonpile-up nonsymmetrical

#### **Mounting Method:**

Threaded bushing single mounting facility

#### Features Provided:

Actuator knob

#### Thready Qty Per Inch (tpi):

32 single mounting facility

#### Thread Size:

0.625 inches 1st mounting facility

#### **Contact Voltage Rating In Volts:**

6.0 lowest ac voltage rating at sea level

#### Switch Actuator Indexing Position Quantity:

3 single actuator

#### **Terminal Type:**

Quick disconnect, male

#### **Contact Switching Action:**

Breaks before makes single section rear

#### Switch Actuator Positioning Increment:

40.0 degrees single actuator

#### Switch Actuator Stop Device Type:

Fixed stop single actuator

#### **Contact Load Current Rating:**

6.0 amperes resistive load highest ac voltage rating at sea level

#### **Precious Material And Location:**

Rivets silver

# NSN 5930-01-086-7484

Rotary Switch - Page 2 of 2

**Precious Material:** 

Silver

Style Designator:

Snap or line

Thread Series Designator:

Un single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0

