NSN 5930-01-086-7484

Rotary Switch - Page 1 of 2



Thread Class:

2a single mounting facility

Thread Length:

0.370 inches single mounting facility and 0.380 inches single mounting facility

Overall Length:

2.985 inches

Overall Diameter:

2.070 inches

Individual Section Quantity:

1

Knob Manufacturer Code:

13445

Knob Manufacturer Part Number:

80101-c

Nonturn Device Type:

Flatted bushing at 12: 00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.625 inches 1st mounting facility

Contact Voltage Rating In Volts:

6.0 lowest ac voltage rating at sea level

Switch Actuator Indexing Position Quantity:

3 single actuator

Terminal Type:

Quick disconnect, male

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

40.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

6.0 amperes resistive load highest ac voltage rating at sea level

Precious Material And Location:

Rivets silver

NSN 5930-01-086-7484Rotary Switch - Page 2 of 2



Precious Material:
Silver
Style Designator:
Snap or line
Thread Series Designator:
Un single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A052b0