# NSN 5930-01-086-9392

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-086-9392

View Online at https://aerobasegroup.com/nsn/5930-01-086-9392	
Body Style:	
Panel mounted	
Hazardous Locations/environmental Protection:	
Corrosion resistant	
Overall Length:	
2.450 inches	
Overall Height:	
1.000 inches	
Overall Width:	
0.750 inches	
Body Width:	
0.485 inches	
Body Height:	
0.740 inches	
Case Material:	
Metal	
Actuator Length:	
0.680 inches	
Actuator Style:	
Rectangular	
Actuator Height:	
0.188 inches	
Actuator Width:	
0.430 inches	
Actuator Color:	
White single actuator	
Illuminated Actuator Color:	
Green single actuator	
Maximum Voltage Rating In Volts:	
115.0 ac and 28.0 dc	
End Application:	
4920-01-064-7974	
Mounting Surface To Terminal End Distance:	
2.200 inches	
Inclosure Type:	
Fully enclosed	
Mounting Method:	
Panel	
Nonpile-up Contact Arrangement:	
2 pole, double throw, one position momentary single switch unit	
Contact Load Current Rating At Maximum Rated Voltage:	

3.000 amperes resistive dc and 1.500 amperes inductive dc and 1.500 amperes lamp dc and 3.000 amperes resistive ac and 1.500 amperes inductive ac and 1.000 amperes lamp ac

## NSN 5930-01-086-9392

Push Switch - Page 2 of 2



#### **Test Data Document:**

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

9 tab, solder lug

## **Specification Data:**

81349-mil-s-22885/58 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0