

View Online at <https://aerobasegroup.com/nsn/5930-01-087-0315>

**Length:**

Between 1.190 inches and 1.260 inches

**Overall Height:**

0.668 inches

**Body Diameter:**

0.640 inches

**Mounting Slot Width:**

0.358 inches

**Body Height:**

0.495 inches

**Unthreaded Mounting Hole Diameter:**

0.140 inches

**Distance Between Mounting Facility Centers:**

0.937 inches

**Temperature Sensing Element Type:**

Internal sensor

**Operating Temperature Rating:**

Between -65.0 degrees fahrenheit and 250.0 degrees fahrenheit

**Mounting Method:**

Unthreaded hole and slot

**Features Provided:**

Hermetically sealed case

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

2.0 amperes resistive load first voltage and 1.0 amperes inductive load first voltage and 500.0 milliamperes lamp load first voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

87.00 actuation point degrees fahrenheit and 75.00 deactuation point degrees fahrenheit

**Contact Voltage Rating In Volts:**

28.0 dc at altitude third voltage

**Frequency In Hertz:**

60.0 first voltage

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0