

View Online at <https://aerobasegroup.com/nsn/5930-01-087-2021>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

0.530 inches

Overall Height:

1.470 inches

Overall Width:

0.330 inches

Bushing Length:

0.470 inches

Body Length:

0.530 inches

Body Width:

0.330 inches

Body Height:

0.400 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.240 inches

Actuator Height:

0.450 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Actuator Color:

Silver single actuator

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

End Application:

6625-01-034-6076

Mounting Surface To Terminal End Distance:

0.550 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 3.000 amperes resistive ac

Precious Material And Location:

Terminal surfaces gold and contacts silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0