

View Online at <https://aerobasegroup.com/nsn/5930-01-087-2674>

**Body Style:**

With side operator

**Hazardous Locations/environmental Protection:**

Raintight

**Overall Length:**

17.250 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

15.125 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

6.813 inches

**Overall Height:**

5.875 inches

**Overall Width:**

10.188 inches

**Body Length:**

17.250 inches

**Body Width:**

8.938 inches

**Body Height:**

5.875 inches

**Unthreaded Mounting Hole Diameter:**

0.312 inches

**Electrical Power Rating At Maximum Ac Voltage Rating:**

7.5 horsepower

**Actuator Style:**

Cast/stamped

**Actuator Height:**

0.250 inches

**Maximum Voltage Rating In Volts:**

240.0 ac

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Plug fuseholder

**Nonpile-up Contact Arrangement:**

3 pole, single throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

100.000 amperes resistive ac

**Test Data Document:**

81348-w-s-865 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

6 screw

**Specification Data:**

81348-w-s-865c government specification

**Specification Or Standard:**

Ld type and 2 class and 2sn design and 3r box

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0