

View Online at <https://aerobasegroup.com/nsn/5930-01-087-2674>

Body Style:

With side operator

Hazardous Locations/environmental Protection:

Raintight

Overall Length:

17.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

15.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

6.813 inches

Overall Height:

5.875 inches

Overall Width:

10.188 inches

Body Length:

17.250 inches

Body Width:

8.938 inches

Body Height:

5.875 inches

Unthreaded Mounting Hole Diameter:

0.312 inches

Electrical Power Rating At Maximum Ac Voltage Rating:

7.5 horsepower

Actuator Style:

Cast/stamped

Actuator Height:

0.250 inches

Maximum Voltage Rating In Volts:

240.0 ac

Mounting Method:

Unthreaded hole

Features Provided:

Plug fuseholder

Nonpile-up Contact Arrangement:

3 pole, single throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

100.000 amperes resistive ac

Test Data Document:

81348-w-s-865 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

6 screw

Specification Data:

81348-w-s-865c government specification

Specification Or Standard:

Ld type and 2 class and 2sn design and 3r box

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0