NSN 5930-01-087-3782

Sensitive Switch - Page 1 of 2

6 screw



View Online at https://aerobasegroup.com/nsn/5930-01-087-3782

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Weatherproof
Overall Length:
3.040 inches
Overall Height:
2.812 inches
Overall Width:
2.125 inches
Actuator Style:
Round
Actuator Diameter:
0.330 inches
Actuator Free Position Height:
2.812 inches
Housing Height:
1.750 inches
Housing Width:
1.000 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.625 inches
Maximum Voltage Rating In Volts:
250.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Switch Release Force:
10.0 ounces
Switch Actuating Force:
Between 26.0 ounces and 59.0 ounces
Actuator Movement:
Between 0.110 pretravel inches and 0.125 overtravel inches and 0.060 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
150.000 milliamperes resistive dc and 10.000 amperes resistive ac
Terminal Type And Quantity:

NSN 5930-01-087-3782

Sensitive Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0