## NSN 5930-01-087-3786

Push Switch - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5930-01-087-3786



## **Body Style:**

Panel mounted

## Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

## **Overall Length:**

3.102 inches

## **Overall Height:**

0.880 inches

#### **Overall Width:**

0.880 inches

- **Body Width:**
- 0.880 inches

## **Body Height:**

0.850 inches

#### Actuator Length:

## 0.750 inches

Actuator Style:

Rectangular

## Actuator Height:

0.155 inches

## Actuator Width:

0.750 inches

## Actuator Color:

White single actuator

## **Illuminated Actuator Color:**

Green single actuator

## **Actuator Inscription:**

High single actuator

## Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

## Mounting Surface To Terminal End Distance:

2.747 inches

Inclosure Type:

Fully enclosed

## **Mounting Method:**

Panel

## **Features Provided:**

Full display lens and rfi shielding

## Nonpile-up Contact Arrangement:

3 pole, double throw, one position momentary single switch unit

## Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 7.500 amperes resistive ac and 5.000 amperes inductive ac and 1.000 amperes lamp ac

# NSN 5930-01-087-3786

Push Switch - Page 2 of 2



Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0