NSN 5930-01-087-9216

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-087-9216

Body Style:
Hole mounted
Overall Length:
1.364 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.875 inches
Overall Height:
1.005 inches
Overall Width:
0.400 inches
Body Length:
1.094 inches
Body Width:
0.400 inches
Body Height:
0.625 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.114 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.406 inches
Actuator Length:
0.110 inches
Actuator Style:
Rectangular
Actuator Height:
0.063 inches
Actuator Width:
0.165 inches
Actuator Free Position Height:
0.578 inches
Maximum Voltage Rating In Volts:
250.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
5.0 ounces
Switch Actuating Force:

8.0 ounces

NSN 5930-01-087-9216

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 5.000 amperes inductive dc and 10.000 amperes resistive ac

Terminal Type And Quantity:

3 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0