NSN 5930-01-087-9972

Sensitive Switch - Page 1 of 2

No



View Online at https://aerobasegroup.com/nsn/5930-01-087-9972

| Body Style: |
|---|
| Hole mounted |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.000 inches |
| Body Length: |
| 1.940 inches |
| Body Width: |
| 0.660 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.140 inches |
| Actuator Length: |
| 1.057 inches |
| Actuator Style: |
| Roller arm |
| Actuator Free Position Height: |
| 0.855 inches |
| Actuator Roller Diameter: |
| 0.190 inches |
| Actuator Roller Width: |
| 0.190 inches |
| Maximum Voltage Rating In Volts: |
| 125.0 ac and 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, one position momentary single switch unit |
| Switch Release Force: |
| 4.0 ounces |
| Switch Actuating Force: |
| Between 10.0 ounces and 22.0 ounces |
| Actuator Movement: |
| Between 0.065 pretravel inches and 0.010 overtravel inches and 0.020 differential inches |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 25.000 amperes resistive dc and 10.000 amperes inductive dc and 1.000 amperes resistive ac and 1.000 amperes inductive ac |
| Terminal Type And Quantity: |
| 3 screw |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| |

NSN 5930-01-087-9972 Sensitive Switch - Page 2 of 2



Fiig:

A053a0