## NSN 5930-01-088-0819

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-088-0819

Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
0.380 inches
Overall Height:
0.350 inches
Overall Width:
0.400 inches
Individual Section Quantity:
1
Operating Tempurature Range:
-10.0/+60.0 degrees celsius
Switch Contact Basic Design:
Coded
Mounting Method:
Printed circuit single mounting facility
Contact Voltage Rating In Volts:
5.0 dc at sea level
Cam Actuated Switch Contact Arrangement:
1 pole, double throw, permanent internal jumpers, both positions maintained single switch single section rear
Switch Actuator Indexing Position Quantity:
10 single actuator
Terminal Type:
Printed circuit
Contact Switching Action:
Breaks before makes single section rear
Switch Actuator Positioning Increment:
36.0 degrees single actuator
Contact Load Current Rating:
100.0 milliamperes resistive load dc at sea level
Contact Arrangement Truth Table:
Bcd, 1 pole - 10 positions single section
Special Features:
Marked w/ 0, 1, 2, 3, 4, 5, 6, 7, 8, 9
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Style Designator:
Miniature panel mount
Specification Data:

12909-404670 manufacturers specification control

## NSN 5930-01-088-0819

Rotary Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0